



PETRONAS Tutela Multi CVT 700

Range:

Long description:

- Exceptional thermal and oxidation stability under high temperature, providing viscosity stability and preventing formation of deposits and sludge to prolong oil life
- Enhanced shear stability for a constant film strength and effective lubrication to protect all moving parts
- Excellent anti-wear, gear and bearing protection to extend components life
- Fuel Economy performance by optimized transmission efficiency

 [Product data sheet](#)

OEM Performance - Only for Automotive: BMW Mini Cooper EZL 799 / EZL 799A / ZF CVT V1 / 83 22 0 136 376/ 83 22 0 429 15 Chery CVT Daihatsu AMMIX CVTF DFE, CVT Fluid DC, CVT Fluid DFE or DFC, Fluid TC Dodge/Jeep/Chrysler NS-2, CVT+4 Ford WSD-M2C-199A Fujijyuuko i-CVTF FG GM/Saturn DEX-CVT, GM CVT Honda HMMF (without starting clutch), HCF2, Z-1 (CVT model, without starting clutch, not Yes for 2001-2007 Honda Fit & Jazz), CVT Hyundai/Kia CVT-1, SP III (CVT) Idemitsu CVTS-EX1 Mazda JWS 3320 MG Rover EM-CVT Mitsubishi CVTF-J1 (MMC Diaqueen CVT Fluid J1), CVTF-J4 and -J4+ (MMC Diaqueen CVT Fluid J4 and J4+), (Diaqueen) SP-III (CVT model only), CVTF ECO J4 Nissan KTF-1, Nissan NS-1, NS-2 and NS-3 Punch CVT Renault Matic CVT Subaru iCVT, iCVT F and FG, ECVT, Lineartronic chain CVT and CVT II Fluid (K0425Y0710), Lineartronic High Torque (HT) CVT Fluid (K0421Y0700), Subaru NS-2 Suzuki CVTF TC, CVTF 3320, CVTF 4401, Suzuki NS-2, CVT Green 1, CVT Green 2, CVT Green 1V Toyota CVTF TC, CVTF FE, Toyota Hybrid Volvo CVT 4959 Audi Multitronic, Audi/VW TL 521 16 (G 052 516), Audi/VW TL 521 80 (G 052 180)

Application(s) - For Consumers pages: Passenger car